


### HOW TO USE OUR PRINTABLE RING SIZER

Open the print dialogue box by pressing CTRL+P simultaneously on your Windows PC, or Command + P if you are using a Mac. Set your printer's scale to 100%, or page scaling/ fit-to-page to "none". Print out this page, then check whether the length from mark "A" and "B" below measures exactly **3.5 inches (88.9 mm)** by using a ruler. If the page is printed correctly, please proceed with the next section.

#### A) TO MEASURE YOUR FINGER:

- 1. Cut around the outline of the ring sizer, taking care not to cut within or beyond the solid line. Then, cut a small slit for Slot "A".
- 2. Thread the pointed end through Slot "A", ensuring the size numbers face outwards. Then, wrap the sizer around the finger on which the ring will be worn.
- 3. Hold one end of the sizer with your thumb, then pull the other end through the slot until the sizer fits snugly around your ring finger. You should feel mild pressure around your finger.
- 4. The size number closest to the slot will determine your ring size. If the reading falls between two figures, such as 15 and 16, choose the larger size (16). After your order is placed, we will send you a solid ring sizer to further verify your size, so you needn't worry too much at this point.
- 5. Measure your finger at room temperature, since cold causes the fingers to shrink.



### B) TO MEASURE A RING:

- Choose a ring that correctly fits the finger of your recipient. If you're choosing a wedding ring, this is customarily the ring finger
  of the left hand.
- Position the ring over the circles until the inner outline of the ring matches the line of the circle. If the ring size falls between two measurements, order the larger size. Caution: If the inside of the ring is domed, match the circle to the domed outline of the ring.





## RING SIZE CHART

CIRCUMFERENCE (MM)	DIAMETER (MM)	England & Australia	NORTH America	Singapore & japan	SWITZERLAND
44.2	14.1	F	3	4	4
44.8	14.3	F ½		5	5 1/4
45.5	14.5	G	3 ½		
46.1	14.7	G ½		6	6 ½
46.8	14.9	Н	4	7	
47.4	15.1	H ½			7 1/4
48.0	15.3	I	4 ½	8	
48.7	15.5	J			9
49.3	15.7	J ½	5	9	
50.0	15.9	K			10
50.6	16.1	K ½	5 ½	10	
51.2	16.3	L			11 ¾
51.9	16.5	L ½	6	11	12 ¾
52.5	16.7	M		12	
53.1	16.9	M ½	6 ½	13	14
53.8	17.1	N			
54.4	17.3	N ½	7	14	15 1/4
55.1	17.5	0			
55.7	17.7	0 ½	7 ½	15	16 ½
56.3	17.9	Р			
57.0	18.1	P ½	8	16	17 ¾
57.2	18.2				
57.6	18.3	Q			
58.3	18.5	Q ½	8 ½	17	
58.9	18.8	R			19
59.5	19.0	R ½	9	18	
60.2	19.2	S			20 1⁄4
60.8	19.4	S ½	9 ½	19	
61.4	19.6	Т			21 ½
62.1	19.8	T ½	10	20	
62.7	20.0	U		21	
63.4	20.2	U ½	10 ½	22	22 ¾
64.0	20.4	V			
64.6	20.6	V ½	11	23	
65.3	20.8	W			25
65.9	21.0	W ½	11 ½	24	
66.6	21.2	X			
67.2	21.4	X ½	12	25	27 ½
67.8	21.6	Y			
68.5	21.8	Z	12 ½	26	28 ¾
69.1	22.0	Z ½			
69.7	22.2		13	27	
70.4	22.4	Z+1			
71.0	22.6		13 ½		



# RING SIZE CHART

CIRCUMFERENCE (MM)	DIAMETER (MM)	CHINA & HONG KONG
44.3	14.1	6
45.2	14.4	7
46.5	14.8	8
47.4	15.1	9
48.4	15.4	10
49.6	15.8	11
50.6	16.1	12
51.8	16.5	13
53.1	16.9	14
54.0	17.2	15
55.3	17.6	16
56.2	17.9	17
57.5	18.3	18
58.4	18.6	19
59.7	19.0	20
60.3	19.2	21
61.2	19.5	22
62.5	19.9	23
63.4	20.2	24
65.0	20.7	25
66.0	21.0	26
66.9	21.3	27
67.8	21.6	28